



Medidas Referenciales / Estimated Dimensions, Acot. mm [pulg.] / Dim. mm [inch.]

**CARACTERÍSTICAS DEL PRODUCTO** **PRODUCT FEATURES**

**UNIDAD PRINCIPAL:**

Voltaje: 110-120 Vca, 50 / 60Hz.  
Potencia: 1050-1250W.  
Presión mínima de operación 0,7 kg/cm<sup>2</sup> / Caudal: (20L / min).  
Presión máxima de operación 8,0 kg/cm<sup>2</sup> (presión hidrostática).  
Cable eléctrico: 1,8 m. de la longitud aproximada. Calibre 16 AWG.

**DISPOSITIVO DE LIMPIEZA:**

Capacidad del contenedor: 600 ml.  
Potencia de calentamiento: 100W.  
Temperatura del agua: 6 ajustes.  
Volumen de agua: 5 ajustes.  
Tipos de limpieza: limpieza trasera / masaje posterior, limpieza frontal para damas.  
Tipos de spray: 5 ajustes.  
Protector de presión de agua: estabilización de presión, descarga de presión automática.  
Dispositivo anti-incrustaciones: dispositivo de descarga de agua rápida, limpieza automática de boquillas, dispositivo anti-sifón, dispositivo anti-incendios.  
Dispositivos de seguridad: controlador de temperatura, fusible térmico, protección de tierra, dispositivo de protección de fuga, prevención de combustión de aire.

**DISPOSITIVO DE SECADO:**

Velocidad del aire caliente: más de 4 m/s.  
Temperatura del viento cálido: 6 ajustes de nivel diferentes.  
Potencia de calentamiento: 250W.  
Dispositivo de seguridad: sensor de temperatura, controlador de temperatura, fusible térmico.

**ASIENTO CON CALEFACCIÓN:**

Temperatura de la superficie: 6 ajustes.  
Potencia de calentamiento: 50W.  
Dispositivo de apertura y cierre: Cierre lento y silencioso.  
Protección del sistema de calefacción: La temperatura del asiento bajará automáticamente al nivel 1 en 10 minutos después de su uso.  
Dispositivos de seguridad: sensor de asiento, sensor de temperatura, controlador de temperatura, fusible térmico.

**SISTEMA INTELIGENTE:**

Conjunto de luz nocturna: inteligente, a menudo en estado apagado.  
Configuración de silencio: Buzzeroff durante la noche.  
Configuración del ID por usuario: Por control remoto para evitar molestias por usuarios múltiples.

**MAIN UNIT:**

Voltage: AC 110-120V, 50/60Hz.  
Power: 1050-1250W.  
Water pressure range: Min. 0,7 kg/cm<sup>2</sup> (20L/min).  
Max. 8,0 kg/cm<sup>2</sup> (Hydrostatic pressure).  
Electrical wire: Length is about 1,8m. 16 AWG gauge.

**CLEANING DEVICE:**

Container capacity: 600ml.  
Heating power: 100W.  
Water temperature: 6 different level adjustment.  
Water volume: 5 different level adjustment.  
Cleansing mode: Rear cleaning/Rear massage, front cleaning for ladies.  
Spray cleansing location: 5 different level adjustment.  
Water pressure protector: Pressure stabilize, automatic pressure discharging.  
Anti-fouling device: Speedy water discharge device, automatic nozzle cleaning, anti-syphon device, air burning preventer.  
Safety device: Temperature controller, thermal fuse, Ground protection, leakage protection device, air burning preventer.

**DRYING DEVICE:**

Warm wind speed: Over 4 m/s.  
Warm wind temperature: 6 different level adjustment.  
Heating power: 250W.  
Safety device: Temperature sensor, temperature controller, thermal fuse.

**HEATED SEAT:**

Surface temperature: 6 different level adjustmen.  
Heating power: 50W  
Open and close device: Quiet soft-closing device.  
Heated burning protection: The seat temperature will automatically lower to level 1 in 10 minutes after using.  
Safety device: Seat sensor, temperature sensor, temperature controller, thermal fuse.

**INTELLIGENT:**

Night light assembly: Intelligent, often in the off state.  
Mute setting: Buzzeroff during night.  
User ID setting: To avoid disturbance from remote controls by multi-user.

**GARANTÍA:**

El producto HELVEX está garantizado como libre de defectos en materiales, mano de obra y procesos de fabricación.

-El producto Helvex y todas sus partes electrónicas están garantizadas por defectos de fabricación y mano de obra por un periodo de 1 año.  
-Las piezas que sufren de desgaste natural en el producto están garantizadas para el uso residencial por 5 años y para el uso comercial por 3 años.

**NORMATIVA:**

Cumple con la norma NOM-003-SCFI-2014.

**WARRANTY:**

The HELVEX product is guaranteed as free from defects in materials, workmanship and manufacturing processes.  
-The Helvex product and all its electronic parts are guaranteed by manufacturing defects and labor for a period of 1 year.  
-The parts that suffer from natural wear and tear on the product are guaranteed for residential use for 5 years and for commercial use for 3 years.

**REGULATIONS:**

It complies with the norm NOM-003-SCFI-2014.

Los productos ilustrados pueden sufrir cambios sin previo aviso en su aspecto o partes, como resultado de los procesos de mejora continua al que están sujetos, sin implicar mayor responsabilidad de la fábrica.

Illustrated products may suffer changes without previous notice in its appearance or parts, as a result of the continuous improvement processes to which they are subject, does not imply greater responsibility of the factory.



Asesoría y Servicio Técnico: 01800 909 2020  
Consultancy and Technical 01(55)53339431  
Service: servicio.tecnico@helvex.com.mx



Refacciones Originales: 01 800 890 0594  
Original Parts: 01 (55) 53 33 94 00  
53 33 94 21  
refacciones@helvex.com.mx Ext. 5068, 5815 y 5913